



## TRI-FLOW® INDUSTRIAL LUBRICANT TF20025, TF20027

- NSF Registration Number 127540, H2 rated
- Lubricates, Penetrates, Protects
- Formulated with P.T.F.E.



CLEANERS, DEGREASERS  
LUBES AND SEALANTS

SUPERIOR  
LUBRICANTS

PAINTS, COATINGS  
AND PRIMERS

CAULKS, SEALANTS  
AND ADHESIVES

BRUSHES, ROLLER COVERS  
AND ACCESSORIES

Tri-Flow® Industrial Lubricant is a superior lubricant containing high-grade petroleum oils, formulated with P.T.F.E., corrosion inhibitors, moisture displacers, penetrating aids and special solvents to soften and remove dirt and corrosion. It is designed to go beyond ordinary lubricants and to keep equipment operating at its peak, even under heavy load, high wear and severe temperature extremes. It is NSF registered, H2 rated.



## PHYSICAL PROPERTIES

**APPEARANCE:** Brown  
**BASE:** Mineral Oil w/P.T.F.E.  
**ODOR:** Mild (fruity)  
**PROPELLANT:** Hydrocarbon  
**LABEL WEIGHT:** 4 oz., 6 oz., 12 oz.  
**SPECIFICATIONS:** NSF Registration 127540, H2 rated  
**WT/GAL:** 6.50 lbs.  
**SPECIFIC GRAVITY:** .78  
**% NON VOLATILE:** 62%  
**% VOC:** 48.20%  
**FALEX LOAD:** 3,000 lbs. per ASTM D-3233  
**FALEX WEAR TEST:** 500 lbs./1 hr. per ASTM D-2670  
**4-BALL WEAR TEST:** 0.8 mm per ASTM D-2266  
**SHELF LIFE:** 3 years  
**FLASH POINT:** <0°F  
**DIELECTRIC STRENGTH:** 10,500 per ASTM D-0877  
**OPERATING TEMPERATURE RANGE:** -60°F to +475°F.  
**HMIS (NFPA RATING):** 2, 4, 0

## USES

- Cables
- Ball and socket joints
- Air power tools
- Conveyors
- Electric power tools
- Glides
- Linkages
- Rollers
- Dies and valves
- Nuts and bolts
- Gears
- Control cables
- Cutting tools
- Drive chains
- Hinges
- Precision tools
- Taps
- Bearings

Distributed By:

## APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale.

### Aerosol Application:

- Product should be sprayed in a well ventilated area.
- Sprays best at room temperature
- Shake well before using
- Spray at a distance of 10" to 14" from surface.

## PACKAGING

Stock No.	Description	UPC Code	NSF Reg. #	NSF Rating	Case Pack
TF20009	Aerosol - 4-oz.	0-32053-20009-0	127540	H2	12
TF20025	Aerosol - 6-oz	0-32053-20025-0	127540	H2	12
TF20027	Aerosol - 12-oz	0-32053-20027-4	127540	H2	12

## RESOURCES

**MSDS/EDS/PRODUCT DATA**

**SHEETS:** [www.paintdocs.com](http://www.paintdocs.com)

**CUSTOMER SERVICE:**

1-800-777-2966

**TECHNICAL INFORMATION:**

1-800-251-2486

**EVERYTHING ELSE  
IS JUST A LUBE!**



**Krylon Products Group**  
 101 Prospect Ave. NW  
 Cleveland, OH 44115  
[www.KPG-Industrial.com](http://www.KPG-Industrial.com)  
 Tel: 1-800-777-2966